




Wireless Temperature Sensor

Rugged for on-metal applications



AZN3256

APPLICATIONS

- Switchgear contactor points
- Electric busbar monitoring
- Predictive maintenance
- Monitor electric motors
- Monitor HVAC efficiency
- Monitor AC switchgear

KEY FEATURES

- Normal temperature range
-40 °C to +85 °C
- Extended High-temperature
up to +125 °C
- Sensor size
13.6 x 9.9 x 4.7 mm
- Battery-free design
- Adhesive backing
- Powered by Magnus® S3

Battery-free equipment monitoring

The AZN3256 is a wireless battery-free temperature sensor. This rugged sensor is designed for switchgear contactor points, busbars, and equipment temperatures in harsh and extreme environments. Other uses include electric motor protection, bearing temperature monitoring, heating, and cooling equipment (HVAC) efficiency monitoring, and other applications where metal surfaces are common.

Wireless temperature sensing

The AZN3256 has a normal operating temperature range of -40 °C to +85 °C. This covers the typical operating temperatures of most equipment over a range of environmental operating conditions. The AZN3256 can be used at extended temperatures beyond its normal operating range to as high as +125 °C, with some loss of Reading accuracy.

Rugged design for use on metal and equipment

The AZN3256 is built with a robust composite antenna and is ideal for harsh environments subject to temperature extremes and elements. The integrated RF antenna harvests energy for the temperature sensing function and communicates with a RAIN/UHF compliant reader. In addition, the integrated antenna is suitable for use on-metal surfaces that might otherwise adversely affect wireless/RF communication range.

Compliance




The AZN3256 is available in FCC and EU/ETSI frequency ranges. The AZN3256 requires a RAIN/UHF compliant reader.




AZN3256 Performance Data

Rugged temperature sensor for on-metal and industrial applications

PARAMETER	VALUE
Normal temperature range	-40 °C to +85 °C
Extended High-temperature	Up to +125 °C, with loss of reading accuracy to approx +/-1 °C
Compatible standards	EPC class 1 gen 2 v2.0.1 ISO 18000-6C
Integrated circuit	Powered by Magnus® S3
TID memory	64-bits
EPC memory	160-bits supporting up to 128-bit EPC
User memory	128-bits
Sensor Size	13.6 x 9.9 x 4.7 mm
Adhesive	Self-stick with an easy-release tab
Shipment method	Packing tray
Minimum order quantity	15 pc MOQ
Ordering information	AZN3256-AFS (FCC 902 to 928 MHz) AZN3256-AES (ETSI 865.6 MHz to 867.6MHz)



©2021 Axzon, Inc. All rights reserved. Reproduction in part or in whole is prohibited without prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. This product is covered by U.S. patents 7586385, 8081043 and other Axzon's granted and pending patents. Visit the Axzon website (<https://axzon.com/patents/>) for latest patent information. Chameleon™ and Magnus® are trademarks of Axzon, Inc. as well as the product and service names mentioned herein are registered trademarks of Axzon, Inc. All other trademarks are the property of their respective owners, Axzon, Austin Texas, USA.



www.axzon.com 代理商联系方式:
样品, 评估板, 参考设计, 报价, 技术支持
电话: 0755-82565851
邮件: dwin100@dwintech.com
手机: 156-2521-4151
网址: <http://www.dwintech.com/rfmicron.html>
深圳市南频科技有限公司
D-Win Technology(HongKong) Co.,Ltd

